



- With integrated self-adhesive strips
- Wind, water and rainproof
- Weatherproof up to 4 months

Packaging

Roll width [m]	Roll length [m]	Roll area [m ²]	Roll mass [kg]
1,5	50	75	14

Characteristics

Material	three-layer polypropene composite
Thickness [mm]	0,50
Specific mass [g/m ²]	150
Water permeability (S _d) [m]	0,03
Resistance to water penetration	W1
Flexibility at low temperature [°C]	≤ -20
Temperature resistance [°C]	-40 to +120
Tensile strength (L/T) [N/50 mm]	315/250
Elongation at maximum tensile strength (L/T) [%]	55/45
Resistance to tearing (nail shank) (L/T) [N/50 mm]	220/230
Reaction to fire (EN 13501-1)	E
Minimum installation temperature [°C]	0



Product description

PAVATEX ADB is a three-layer polypropene vapour permeable sarking membrane with integrated self-adhesive strips. The membrane is used in combination with PAVATEX insulation boards such as PAVATHERM and ISOLAIR. The longitudinal joints are sealed using the integrated self-adhesive strips. The horizontal joints are sealed with PAVATAPE 12. Screws and plugs are sealed with PAVAFIX SN TAPE. Connections and penetrations are sealed with PAVATEX sealing products. If mechanically fastened, PAVATEX ADB can be left exposed to weathering for up to 4 months. Always consult the local regulations and installation guidelines of the manufacturer.

Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

Storage

Store cool and dry, lying down or upright, protected from sunlight.