



- Solvent-free and without odour
- Permanent elastic bonding, adheres to moist surfaces
- Sealing of overlaps and connections of PAVATEX membranes and as adhesive medium for PAVATAPE

## Packaging

	Contents per container [ml/g]	Box contents [units]	Accessories included
Cartridge	310/470	12	12 detachable nozzles
Tubular bag	600/900	10	10 large conical nozzles

## Characteristics

Material	solvent-free 1-component polyurethane adhesive
Minimum application temperature substrate and ambient [°C]	-5
Application temperature product [°C]	+5 to +40
Temperature resistance [°C]	-40 to +110
Application time (skin formation) at 20 °C and 65 % r.h. [min.]	7
Tight after [h]	2

## Product description

For waterproof and weatherproof gluing of PAVATEX insulation and sarking systems, for waterproof and airtight gluing of overlaps and connections of PAVATEX membranes. As adhesive medium for PAVATAPE on moist and porous substrates. Also adheres to wood, wooden boards, non-combustible construction boards, concrete, brickwork, render, corrosion-protected metals and damp substrates.

## Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

For more information, please refer to the relevant safety data sheet.

## Storage

Shelf life: 18 months unopened  
Store cool and dry, protected from sunlight.