

MultiTrack 1000

Nonwoven Geotextile, 1500N, 100g/m² - 4.5m x 100m roll



UK
CA CE

PRODUCT NAME	DESCRIPTION
MultiTrack 1000	Nonwoven Geotextile, 1500N, 100g/m ² - 4.5m x 100m roll

Details

Third party certified		CE UKCA
Tensile strength (MD)	EN ISO 10319	8kN/m
Tensile strength (CMD)	EN ISO 10319	8kN/m
Elongation at max load (MD)	EN ISO 10319	45%
Elongation at max load (CMD)	EN ISO 10319	55%
Dynamic perforation resistance	EN ISO 13433	34mm
CBR puncture resistance	EN ISO 12236	1500N
Dynamic cone drop	EN ISO 13433	34mm
Water permeability	EN ISO 11058	110L/m ² .s
Characteristic opening size	EN ISO 12956	120µm
Thickness under 2kPa	EN ISO 9863-1	1mm
Weight	EN ISO 9864	100g/m ²
Roll width		4.5m
Roll length		100m

Roll diameter

29cm

Notes

1. Other grades are available on request
2. Other roll sizes are available on request
3. Calculated for given roll dimensions and standard truck (2.4 x 2.65 x 13.6 m)

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.

2. It is the responsibility of all users to satisfy themselves the above data is current.

3. Installation details are available on request.



FM32898

