



- Interior finishing board
- Ideal for the coverage of loose fill on floors
- Underlay board for parquet / laminate

## Packaging

Thickness [mm]	Boards/pallet	Dimensions [mm]	m <sup>2</sup> /pallet [m <sup>2</sup> ]	Mass/pallet [kg]	Thermal resistance (R <sub>d</sub> ) [m <sup>2</sup> .K/W]
8	276	1200 x 600	198,72	366	0,15
10	114	2500 x 1200	342,00	787	0,20
12	95	2500 x 1200	285,00	787	0,20
16	70	2500 x 1200	210,00	773	0,30
19	60	2500 x 1200	180,00	787	0,35

\* Other dimensions available on request

## Characteristics

Density [kg/m <sup>3</sup> ]	230
Thermal conductivity (λ <sub>d</sub> ) (EN 12664) [W/(m.K)]	0,050
Specific heat capacity (c) [J/(kg.K)]	2100
Water vapour diffusion resistance coefficient (EN 12572) [μ]	0
Reaction to fire (EN 13501-1)	E
Compressive strength at 10 % deformation [kPa]	100
Waste code according to The European Waste Catalogue (EWC)	030105; 170201
Edge profile	straight

NPD = no performance determined



## Product description

PAVANATUR is a natural and ecological, thermal and contact sound-insulation board based on wood fiber.

Always consult the local regulations and installation guidelines of the manufacturer.

## Health, Environment and Safety

The product does not contain any substance which is likely to be detrimental to health or to environment and complies with generally admitted Health and Safety Requirements.

## Storage

Store the insulation boards on a flat surface, keep dry and protected from sunlight.

Stack no more than 4 pallets on top of each other.