

Batilys Color

Natural hydraulic lime colored mortar



+ Products

- Colored natural hydraulic lime mortar (32 colors available)
- Packaging adapted to the different types of construction sites (bag and big bag)
- Specific addition to eased the setting

Batilys color is a colored hydraulic lime mortar for laying and grouting terracotta, raw earth and natural stone.

Description

- It allows to layand join terracotta, raw earth and natural stone
- Its specific adjuvantation gives it a flexibility facilitating its implementation
- Standard: EN 998-2

Properties

- Resistance suitable for soft materials
- Flexible and unctuous mortar, easy to implement
- Optimized grip to supports
- Optimal productivity on site (colored mortar) only water need to be added



Reference documents

- DTU 20.1
- Standard NF EN 998-2

Performance

- Recipe mortars

Composition

- Hydraulic lime
- Calcareous fillers
- Additives

Implementation

- · Moisten the supports before implementation
- · Apply the mortar in horizontal and vertical parts
- · Carry out the grouting
- Water dosage: 4l of water for a 25 kg bag to be adjusted according to the climatic conditions and the consistency of the mortar.
- Mixing time: a minimum of 3 minutes
- **Consumption**: For a thickness of 10 mm of solid surface of a brick of 28 cm x 10 cm x 5 cm with vertical joints, the consumption is 25-30 kg.

Acceptable support

- Terracotta
- Earthen
- Natural stone

Excluded supports

- Materials covered with paints
- Gypsum-based products (plaster)

Material

Cement mixerPlaster Mixer

Packaging

- Big Bag 1 T

- 25kg bag, 56 bags per pallet or 1.4 T

Technical assistance

- At the start of the construction site

Color Range



2 Castans district 65370 Izaourt Tel. 05 62 99 33 99

